



# LEICA TRINOVID BCA 25 mm

## Technical Data



|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| <b>Binocular</b>                          | <b>LEICA TRINOVID<br/>10 x 25 BCA</b>        |
| <b>Order No. Product</b>                  |                                              |
| <b>Amored, black</b>                      | 40 343                                       |
| <b>Delivery scope</b>                     | Carrying cord, Cordular case with belt loop  |
| <b>Magnification</b>                      | 10 x                                         |
| <b>Front lens diameter</b>                | 25 mm                                        |
| <b>Exit pupil</b>                         | 2.5 mm                                       |
| <b>Twilight factor</b>                    | 15.8                                         |
| <b>Field of view at 1,000 m</b>           | 90 m                                         |
| <b>Field of view at 1,000 yds</b>         | 273 ft                                       |
| <b>Eye-relief</b>                         | 14.6 mm                                      |
| <b>Objective angle of view</b>            | 5.2°                                         |
| <b>Close focusing distance</b>            | approx. 5 m/ 16.4 ft                         |
| <b>Diopter compensation</b>               | ± 3.5 diopters                               |
| <b>Eyepieces for eyeglass wearers</b>     | yes                                          |
| <b>Sliding eyecups</b>                    | extendable eyecups                           |
| <b>Adjustable interpupillary distance</b> | 32–74 mm                                     |
| <b>Focusing</b>                           | Internal focusing via central focusing knob  |
| <b>No. of lens elements (each side)</b>   | 6, all with HDC™ coating                     |
| <b>Prism system</b>                       | Roof prism with phase correcting coating P40 |
| <b>Watertightness</b>                     | Waterspray resistant                         |
| <b>Housing</b>                            | Aluminum                                     |
| <b>Dimensions (W x H x D)</b>             | 110 x 92 x 37 mm<br>4 3⁄8 x 3 5⁄8 x 1 1⁄2 in |
| <b>Weight</b>                             | approx. 255 g / 9 oz                         |